Location:	Leicester Outdoor Pursuits Centre	Date of Assessment:	27/9/12	Last Reviewed: Dec 22	Name of Assessor:	Chris Murnin
Activity:	Use of hoist (to transfer in and out of boats )	Assessment Reference No:	4.35	KG	Signature of Assessor:	Cohin

ITEM/ HAZARD	CONTROL MEASURES	
Incorrect lifting and	All staff to lift and carry hoist sections in line with manual handling training and guidelines.	
carrying	Where possible two people to work together setting up hoist.	
	If any doubt regarding correct set up, refer to management	
Inserting mast into base	Fingers must be kept clear of the spigot that inserts into the base.	
	Mast to be lowered in a controlled fashion.	
Incorrect assembly	<ul> <li>Hoist must be assembled by staff that have been trained.</li> </ul>	
	<ul> <li>Hoist only to be assembled in line with the owner's manual and LOPC guidelines.</li> </ul>	
	Spreader bar locking screw must be tightened.	
	All orange parts to be checked for tightness and correct location.	
Structural failure	Hoist to be inspected in line with LOLER every 6 months.	
randro	<ul> <li>Hoist must be assembled in line with the owner's manual and LOPC guidelines and training.</li> </ul>	
	Staff to visually check assembled hoist before use.	
	Hoist only to be assembled and used by trained staff.	
Banging head into structure	Awareness of surroundings.	
into otraotaro	Slings setup in line with training- and manufacturers guidelines.	
	Instructor care and attention.	
Incorrect sling used	Size charts to be used to check correct sizing is used.	
	Training to cover sling selection.	
	Guidance from individual and visiting staff.	
Inappropriate physical	Support staff to fit slings where possible.	
contact	<ul> <li>Individuals to assist with fitting of their sling where possible.</li> </ul>	



	LOPC training to cover use of slings.
	Instructor communication with individual detailing upcoming actions.
Falling in the river	Awareness of surroundings.
	Buoyancy aids must be worn by all involved in the hoisting process the area when the hoist is in use.
	Surrounding area to be kept clear of surplus people and vacant wheelchairs.
Wheelchairs rolling away	Vacant wheelchairs to be cleared out of the way.
· · · · · · · · · · · · · · · · · · ·	Wheelchair brakes to be applied.
Overreaching	Participant only to be lowered into the part of the boat near the riverbank.
	Boats to be moved into the best position for participants.
Uncontrolled landing	Staff used to aid person into the boat or chair.
······································	Individual encouraged to help themselves.
	Communication between staff.
	Careful control of the ram knob.
Ram falling	Ensure webbing strap is around ram before lifting, carrying or dismantling.
Unauthorised / mis-use	Hoist to be stored securely inside when not in use.
	Staff to setup hoist at latest available opportunity.
	Staff to put hoist away at the earliest available opportunity.

